

Manufactured in B.C.

Various species, long length, wide plank, single strip Engineered Hardwood flooring

Configuration:	9/16" x 5.25" or 7.25"
Face Layer:	4mm sawn hardwood.
Lengths:	2' - 10', Heavy 7' - 10'
Core:	Baltic Birch ply, Exterior Glue (Meets European E-1 standard)
Moisture:	8 % +/- 1%
Finish:	UV cured Acrylic, Oxidative or UV cured Oils
Colours:	Common Standard range or Custom colours
Surface Treatment:	Smooth, with slight texture or light wire brushed.
T&G Machining:	Standard T&G, beveled 4 edges
Hardwood Species:	White or Red Oak, Black Walnut, Sapele, Ash plus others.
West Coast species:	Douglas Fir, Western Maple, Hemlock, Larch
Grades:	White Oak is normally Select grade, though Rustic is available. Black Walnut grading differs -consult. Softwoods are available in several "looks" - consult.

NOTE - Characteristics vary and should not be specified from single samples. We do not guarantee that colors will match any particular sample due to the variety of color within any specie. All woods vary in colour & density affecting absorption of stains resulting in variations.

Installation: We recommend full spread glue down, however these may be installed using "float-in" technique, or cleating.

Heated floors: Radiant floor installation guide must be followed. Customers must be informed of limitations & what to expect when heating causes drying, shrinkage & possibility of cracking. Maintenance: See Maintenance guides for wood floors or www.Woodfloors.org

Installation site: Site conditions must be within industry guidelines as to humidity, Sub-floor Moisture, PH if gluing, etc. Humidifiers or de-humidifiers recommended for RH control between 30 - 50%

Warranty: See [Warranty publication](#).